

TASCHEN-BANDMASSE

POCKET TAPES

01

W-Thick



Geprägte Oberfläche zur Vermeidung von Reflexionen
Embossed finish to prevent reflection

Transparentes Nylon
Transparent nylon

Beschichtung mit Spezialharz
Bake coating with special resin

Bedruckte Skala
Printed scale

Vorverarbeitung
Preprocessing

Die Spitze ist aus Stahl
Steel

The tape that does
NOT FEAR WATER!

W-Thick



Die Feder besteht aus rostfreiem Edelstahl, welche die Wicklung deutlich verbessert.

The spring is made of rust-resistant stainless, greatly improved winding problems.

Leistungsvergleich W-Thick

W-Thick performance comparison

Product	W-Thick	A	B	C
Tape coating	Nylon (coating)	Nylon (painting)		
Tape length x width	5 m × 25 mm	8 m × 25 mm	5 m × 19 mm	5 m × 16 mm
Tape wear resistance ※ 1	1,000 or more reciprocations	Less than 50 reciprocations	Less than 150 reciprocations	Less than 50 reciprocations
Superior Stand-Out	2.3 m	2.2 m	2.1 m	1.1 m
Rigidity (N) ※ 2	Front surface	8.2	5.5	3.9
	Back surface	37.2	26.7	18.6
Hook strength (N) ※ 3	1,503	586	612	909

※1 They let an eraser made of sand go and back on a tape. The number indicates "how many times" an eraser did this action until the scale will be unreadable.

※2 This is our own/original way of showing how rigid the tape is, not will be bent or warped.

The number indicates the force exactly the moment when tape snaps by being added force.

※3 It indicates the maximum strength of the nail by falling.

It means, you drop Conve (tape sotred inside) but still the nail will not be broken.



More info



Art.Nr.			Tape Measurement Accuracy	CASE	MASTER CARTON	EAN	Weight (g) (Packaging + Product)
GASP25-50EB-EUR	25 mm	5 m	EC Class 2	6	30 (5 SETS)	4975364 122063	2,287 (358/pc)